

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A mounting for a device (3) for the optical monitoring of a woven material web (2) on a loom (1), including a mounting (5), in which the monitoring device (3) extends over the entire width of the woven material web, in which the monitoring device (3) is mounted, indirectly connected to the loom (1), in contact with the woven material web (2) in the region (6) between a take-off roller (30) and the point at which the material web (2) is wound onto a loom beam (10) or onto a large-scale winding roller and parallel thereto, ~~characterised in that~~ wherein this mounting comprises an axis (7) on the monitoring device (3) and an axis (8) on the loom (1), and the two axes (7, 8) extend parallel to one another and are connected to one another by way of a pivotal arm (9).

2. (Currently Amended) A mounting according to Claim 1, ~~characterised in that~~ wherein the mounting (5) on the axis (8) connected to the loom (1) is performed by means of a sleeve (12) formed by two half- shells (11), with the pivotal arm (9) secured to one half- shell (11).

3. (Currently Amended) A mounting according to Claim 2, ~~characterised in that~~ wherein the pivotal arm (9) is connected in one piece with one of the two half-shells (14).

4. (Currently Amended) A mounting according to Claim 2, ~~characterised in that~~ wherein to each side of the monitoring device (3) there is arranged a bearing pin (13), with the bearing pins lying in a straight line and forming the axis (7) of the monitoring device (3).

5. (Currently Amended) A mounting according to Claim 1, ~~characterised in that~~ wherein a bearing housing (14) is integrally formed with the pivotal arm (9) and the bearing pins (13) of the monitoring device (3) are mounted pivotally in this bearing housing (14), and ~~in that~~ wherein a pin (15) extending parallel to the bearing pin (13) is borne such that it may be clamped and pivoted in an arcuate slot (16) for the angular positioning of the monitoring device (3).

6. (Currently Amended) A mounting according to Claim 1, ~~characterised in that~~ wherein the pivotal arm (9) is in the form of a rod which is provided at both ends with a clampable bearing (17) capable of angular adjustment.

7. (Currently Amended) A mounting according to claim 1, ~~characterised in that~~ wherein it holds the monitoring device (3) such that it may pivot about both axes (7,

8) to lie against the material web in the region (6) in the vicinity of an expanding roller or a deflection roller (33) of the loom (1).

8. (Currently Amended) A device according to Claim 7, ~~characterised in that~~ wherein the mounting holds the monitoring device (3) such that it may pivot about both axes (7, 8) to lie against the material web in the region (6) directly upstream, in relation to the direction of transport of the textile material web (2), of the expanding or deflection roller (33).

9. (Currently Amended) A device according to Claim 7, ~~characterised in that~~ wherein the mounting holds the monitoring device (3) such that it may pivot about both axes (7, 8) to lie against the material web in the region (6) directly downstream, in relation to the direction of transport of the textile material web (2), of the expanding or deflection roller (33).